

Modelling effects of spatiotemporal temperature variation on native and alien fish species in riverine ecosystems using thermal imagery

Frank Collas^{a,b,*}, Wimala van Iersel^c, Menno Straatsma^c, Rob Leuven^{a,b} ^a Radboud University, Department of Animal Ecology and Ecophysiology, Institute for Water and Wetland Research, The Netherlands ^b Netherlands Centre of Expertise on Exotic Species (NEC-E), Nijmegen, The Netherlands ^c Utrecht University, Geosciences, Utrecht, The Netherlands

Keywords ---biodiversity; remote sensing; river rehabilitation; species sensitivity distributions, UAV

Introduction

Environmental stressors such as global warming and invasive alien species are increasingly impacting riverine ecosystems, thereby influencing water usage and biodiversity (Leuven et al. 2011; Van Vliet et al. 2013).

Water temperature is a key factor affecting distribution of native and alien freshwater fish species. When temperatures become too high detrimental stress occurs in many species ultimately resulting in mortality. The thermal limits of fish species were used to derive species sensitivity distributions (SSDs; Leuven et al. 2011), which allow to predict potentially affected fractions and habitat suitability in relation to changing water temperature regimes.

As water temperature of riverine ecosystems are expected to increase, thermal limits of fish species can be exceeded, urging the need to assess effects of ecological rehabilitation measures temperature on regimes of rivers. Recently, several side channels have been built in the floodplains of the river Rhine, though temperature regimes remain unclear.

The high spatiotemporal variability of water temperature limits the use of point measurements to accurately assess effects on fish species in rivers and side channels (Leuven et al. 2011). Potentially, unmanned airborne vehicles (UAVs) could provide temperature field with a spatial resolution of less than 1 m depending on flight elevation. UAVs can be employed with a thermal infrared sensor, potentially enabling spatial monitoring of water temperature in side-channels with a width up to 30 m.

The temperature of an object can be derived from its thermal infrared radiation (TIR) after correction for its emissivity. Water temperature assessed with remote sensing

Email address: f.collas@science.ru.nl (F..Collas) URL:http://www.ru.nl/environmentalscience/staff/individ ual-staff/collas/ (F. Collas) measures only the upper 0.1 mm of the water column (Handcock et al., 2012). The highly reflective water surface can disturb the thermal signal of the water by reflecting thermal radiation from the sun and surrounding objects via the water surface into the sensor (Anderson and Wilson, 1984). This effect varies over time, due to changes in solar angle and wind conditions. Hence, it remains unclear whether water temperature can be estimated with sufficient accuracy for freshwater fish habitat monitoring using UAV thermal imagery.

The present research aims to predict the ecological potential of a side channel during a hot summer day using UAV derived water temperature measurements. The research questions are: 1) How accurate can water temperature in side-channels be measured using UAV thermal imagery? 2) What is the spatiotemporal temperature variation of a side channel during a summer day? 3) What is the ecological potential of a side channel taking water temperature into account?

Method

Monitoring consisted of simultaneously collecting thermal imagery using a UAV and in-situ water temperature measurements using temperature loggers. The Sensefly Ebee UAV (SenseFly, 2017) employed with the ThermoMAP sensor was used to collect thermal imagery at 07:15h, 13:00h, 15:00h and 19:30h on August 29th 2017. Flight duration was approximately 15 minutes. In-situ water measurements were carried out with the Hobo Onset sensor 10 cm below the water surface at locations distributed across the side 24 channel covering variation in its depth and width. Before each flight, the vertical position of each logger was adjusted to ensure the positioning at 10 cm below the water surface. The loggers measured water temperature with a frequency of 0.1 Hz.

The UAV imagery were processed into orthophotos using SenseFly Postflight Terra. UAV imagery was geo-referenced using 23 ground control points. The TIR values of the

^{*} Corresponding author



orthophotos were converted to temperature (T_{UAV}) with eq. 1:

$$T_{UAV}$$
 (°C) = TIR / 100 – 100 (1)

We validated the T_{UAV} with median temperature of *in-situ* reference data over the time interval of the corresponding flight (T_{ref}). Subsequently, a linear regression was used to analyse the relation between T_{UAV} and T_{ref} for each flight separately.

We created a temperature map by applying the the regression equations to the T_{RS} map. Subsequently, we calculated the potentially not occurring fraction (PNOF) of native and alien freshwater fish based on the river specific species sensitivity distribution (SSD) of alien and native fish published by Leuven et al. (2011) and the temperature maps.

Results and discussion

 T_{ref} was estimated with a mean absolute error (MAE) of $0.81\pm0.61^{\circ}$ C by T_{RS} . Lower temperatures (< 24°C) of the morning flight were mostly underestimated and higher temperatures during the afternoon were overestimated (Figure 1).

The regression equation of the afternoon flight at 15:00 had an intercept close to zero and slope close to one. The morning and early afternoon flight performed the worst with an R^2 of 0.45 and 0.57, respectively. These results show that UAVs with a ThermoMAP sensor can be used to spatially explicit measure ambient water temperature, but the accuracy varies during the day.

Water temperature in the side-channel was lower in the morning compared to the main channel. A reversed pattern was observed



Figure 1. Linear regressions of UAV ThermoMAP sensed temperatures and in-situ temperature measurements for each of the separate flights. Light grey line is y=x; Black dashed line reflects the overall linear regression.

during the afternoon.

The PNOF maps showed a limitation of habitat suitability for native and alien fish species throughout the day (Figure 2). Native species were more limited in the side channel compared to alien species. The highest limitation occurred during the afternoon when water temperatures were close to 28°C. These results show that under hot summer conditions the function of side-channels as refugia for cold water species is limited. In order to increase the ecological value of the side channels, flow velocity and depth could be increased thereby reducing water temperatures. Moreover, side channels in areas with high seepage of groundwater are expected to be more suitable for native cold water fish species.



Figure 2. Potentially not occurring fraction of alien and native fish species at 07:15h, August 29th 2017.

Acknowledgements

This research comprises part of the research programme RiverCare and is financially supported by the Dutch Technology Foundation STW (Perspective Programme, grant number P12-14).

References

- Anderson, J.M. and S.B. Wilson (1984). The physical basis of current infrared remote-sensing techniques and the interpretation of data from aerial surveys. International Journal of Remote Sensing 5 : 1-18.
- Handcock, R.N., C.E. Torgersen, K.A. Cherkauer, A.R. Gillespie, K. Tockner, R.N. Faux, and J. Tan (2012). Thermal infrared remote sensing of water temperature in riverine landscapes. Fluvial Remote Sensing for Science and Management, 85-113.
- Leuven, R. Š. E. W., A. J. Hendriks, M. A. J. Huijbregts, H. J. R. Lenders, J. Matthews and G. van der Velde (2011). Differences in sensitivity of native and exotic fish species to changes in river temperature. Current Zoology 57:852-862.
- Van Vliet, M. T. H., W. H. P. Franssen, J. R. Yearsley, F. Ludwig, I. Haddeland, D. P. Lettenmaier and P. Kabat. (2013). Global river discharge and water temperature under climate change. Global Environmental Change 23:450-464.